

DIESEL WATER SEPARATORS



Innovations in Purification

Email: sales@deltafilts.com

Call: 91-9930073977

Skype: deltafilts

Web: www.deltafilts.com

DELTA Diesel Water Separators

provide the best solution for achieving high degree of water separation from Diesel Fuel. A two stage solution via Coalescer and Separator stages provides superior quality of Fuel. The Diesel Fuel is free from water down to 15 ppm. The first stage is the coalescer stage wherein the Fuel flows inside to outside of the Coalescer Elements. The Coalescer elements are rated at 1 Micron and activate the process of Coalescence i.e. combination of small water droplets to form bulk water. Since water has a higher specific gravity than Fuel, it settles down into the Sump. The fuel free from water then flows through the second stage i.e. Separator stage. The flow direction is outside to inside during which the separator element repels any traces of water droplets and hence allowing only clean dry fuel to exit the Filter Vessel.

SALIENT FEATURES:

- Filters Vessels designed as per ASME Code
- 100% Radiography of all Butt Weld Joints
- With Two Stage Coalescer & Separator Elements
- Particulate Filtration down to 1 Micron, Water removal down to 15 ppm
- Isolation Valves, Drain, Vent and Safety Valves (Optional)
- With Differential Pressure Gauges, Pressure Gauge on Front Panel (Optional)
- Available in both Vertical and Horizontal Orientation



www.deltafilts.com
Diesel Water Separator
1500 LPM Flow Rate

Vertical Diesel Water Separator for 1500 LPM Flow Capacity



Horizontal Diesel Fuel Water Separator for 200 LPM Flow Capacity

DELTA DIESEL WATER SEPARATOR MODELS

MODEL	LINE SIZE (NB) ¹	END CONNECTION ²	FUEL FLOW RATE (LPM) ³	HOUSING MOC ⁴	ELEMENT SET CODE
DWS-100	1"	ASA 150	50	Carbon Steel	DE421
DWS-200	2"	ASA 150	100	Carbon Steel	DE830
DWS-250	2½"	ASA 150	250	Carbon Steel	DE845
DWS-300	3"	ASA 150	500	Carbon Steel	DE860
DWS-400	4"	ASA 150	1000	Carbon Steel	DE875
DWS-600	6"	ASA 150	1500	Carbon Steel	DE875

1. Larger sizes available on request to serve higher Fuel flow rates
2. Other Flange Standards can be provided as per customer requirement
3. Flow Rate specified for Diesel Fuel. Contact us for Aviation Fuel Flow Rates.
4. Can be provided in SS304 / SS316 MOC if required

MATERIAL OF CONSTRUCTION

1. Filter Housing:	A106 Gr. B / SA 516 Gr. 70
2. Gasket:	SS304 Spiral Wound, GRAFOIL Filled (Non-Asbestos)
3. Filter Media:	Glass Fibre
4. Fasteners:	High Tensile ASTM A 193 Gr. B7 + A 194 2H
5. Paint:	Epoxy Based Primer + Epoxy Final Shade

APPLICATIONS

- Upstream of **Diesel Engines** to protect engine from water contamination
- Marine **Diesel** Applications – on Board Ships
- **Diesel Fuel** Loading / Unloading and in Refineries for high purity Fuel Delivery

DELTA FILTERS & SEPARATORS PVT LTD

B-101 Sanpada Station Complex, Sanpada, Navi Mumbai 400 705 INDIA
 Tel: 91-22-2775 2357 Fax: 91-22-2775 5105 Mobile: 91-9930073977
 Email: sales@deltafilters.com & akini@deltafilters.com Website: www.deltafilters.com